## **Pneumatic Forklifts**

Pneumatic lift trucks are often called pallet lift trucks or pump trucks and are commonly used in warehouses and delivery facilities to move resources on pallets. Pneumatic lift trucks comprises a pair of metallic forks mounted on a wheeled counterweight that has a pump. The pump is used to lift and lower the forks.

It is essential to visually check the pallet truck prior to loading any resources and to make certain the handles move smoothly, the pallet lift turns appropriately, and the lift is free of any potential obstacles. Inspect the freight to make certain that there will be minimal opportunities for anything to fall off during lifting and moving. Discharge any air in the pump and drop the forks to the ground by squeezing the handle installed on the inside of the metal loop on the end of the handle. Run the blades into the slots in the pallet and ensure the blades are centered so that the palletsâ?? mass is evenly distributed.

Pump the pneumatic lift lever up and down to lift the blades from the floor. Stop pumping as soon as the pallet is entirely off the ground as there is no need to lift it any higher or risk losing stability while turning. In order to shift the pallet, drag the handle behind you; you should not push it. There will be a large amount of momentum existing. Avoid quick or sharp turns and you should not stop too abruptly. Gently bring the pallet to a halt wherever you would like to park it. Squeeze the handle within the handle end to return the blades to the ground. Withdraw the forks and return the pallet jack to a fitting parking area or continue onto the next task.